

SPECIFICATIONS



Model Name	SBL-30X30x x=R,G,B,W				
Input Voltage	DC24V (Please use within 24V, otherwise it may cause temperature rise or could diminish the lifetime)				
Current Consumption	0.07A				
Power Consumption	1.6W				
LED Color	Red	Green	Blue	White	
Peak Wavelength (typ.)	635nm	525nm	470nm	6000K	
Connector	3-prong connector , SMR-03V-B/ Manufacture: JST				
Polarity & Signal	1: Anode (+)brown 2: NC 3: Cathode (-)blue				
Operating Conditions	Temp. 0 - 40°C (Light intensity may vary due to the change in ambient temperature) Temp. 0 - 40°C, Humidity 20 - 85% (non-condensing) (Should not be frozen, condensed or exposed to the rapid change in temperature)				
Storage Conditions	Temp. -20 - 60°C				
	Humidity 20 - 85% (non-condensing)				
Exterior Dimensions	Refer to the drawing on a separate sheet				
Environmental Regulation	CE , RoHS , IEC 62471 Compliant Product (REACH Compliant Product)				
Special Instruction					

CCS Asia Pte Ltd

35 Marsiling Industrial Estate Road 3 #05-03, Singapore 739257

TEL : +65-6363-1180 FAX : +65-6363-1236 e-mail : sales@ccs-asia.com.sg