

SPECIFICATIONS



| | | | | | |
|--------------------------|--|--------------|-------|-------|-------|
| Model Name | SL-75X30x | x=R,G,B,W,IR | | | |
| Input Voltage | DC24V (Please use within 24V, otherwise it may cause temperature rise or could diminish the lifetime) | | | | |
| LED Color | White | Red | Green | Blue | IR |
| Peak Wavelength (typ.) | 5500K | 630nm | 525nm | 470nm | 940nm |
| Input Current | 0.24A | 0.18A | | | |
| Power Consumption | 6.1W | 4.6W | | | |
| Connector | 3-prong connector , SMR-03V-B/ Manufacture: JST | | | | |
| Polarity & Signal | 1: Anode (+)brown 2: NC 3: Cathode (-)blue | | | | |
| Operating Conditions | Temp. 0 - 40°C (Light intensity may vary due to the change in ambient temperature) Temp. 0 - 40°C, Humidity 20 - 85% (non-condensing) (Should not be frozen, condensed or exposed to the rapid change in temperature) | | | | |
| Storage Conditions | Temp. -20 - 60°C | | | | |
| | Humidity 20 - 85% (non-condensing) | | | | |
| Exterior Dimensions | Refer to the drawing on a separate sheet | | | | |
| Environmental Regulation | CE , RoHS , IEC 62471 Compliant Product (REACH Compliant Product) | | | | |
| Options | Diffuser : DF-SL-75X30 , Polarizer : PL-SL-75X30 | | | | |
| Special Instruction | | | | | |

CCS Asia Pte Ltd

35 Marsiling Industrial Estate Road 3 #05-03, Singapore 739257

TEL : +65-6363-1180 FAX : +65-6363-1236 e-mail : sales@ccs-asia.com.sg